

1190

FORTE



SPECIFICATIONS:

Forward throw
 0.8 kg
 CRI 82+
 CRI 70+
 Class I
 IP65
 CE
 5 Year warranty
 Made in Australia

CONSTRUCTION & DESIGN

- Recessed LED exterior wall light
- Constructed in pressure die cast aluminium alloy and finished in durable polyester powder-coat paint
- Robust housing for superior durability
- Recessed luminaire with glare free illumination
- Frosted tempered glass, silicone seals and stainless steel fasteners provide IP65 protection
- Plastic installation box included with each fitting to facilitate installation and maintenance
- Recessed and baffled light source provides 35° forward throw illumination

OPTICAL & THERMAL PERFORMANCE

- LED thermal management incorporates conduction to transfer heat rapidly away from LED source with optimal performance

ELECTRICAL SYSTEM

- Supplied standard with an integral leading and trailing edge mains dimmable driver and terminal block (refer to dimming options table)
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz


TECHNICAL PERFORMANCE

- 8W or 13W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (macAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ is available upon request

CODE ORDERING GUIDE: PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1190-3K-8W-07 or 1190-3K-8W/DALI-07

SYSTEM POWER	COLOUR TEMP.	72x34° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
				72x34°
PRODUCT CODE				
8W	3K		828	182
	4K		870	193
	5K		845	188
13W	3K		1519	303
	4K		1607	321
	5K		1568	312



DIM CODE	OPTIONS	8W	13W
/DALI	Dali Dimming / Switch Dim	✓	✓
/DSI	Digital Dimming	x	x
/AD	Analogue Dimming 1-10V	x	x
/DIM	Leading & Trailing edge	Std	Std

COLOUR CODE	COLOUR
-07	Textured Black

INSTALLATION BOX

