



SPECIFICATIONS:

0.3 kg	CRI 82+ 3K and 4K	CRI 70+ 5K	115	SELV	IP65	CE	5 Year warranty	Made in Australia
--------	----------------------	---------------	-----	------	------	----	--------------------	-------------------

CONSTRUCTION & DESIGN

- Recessed LED downlight with frosted diffuser
- Constructed in die cast aluminium alloy and finished in durable polyester powder-coat paint
- Recessed primary optics and secondary polycarbonate diffuser gives a symmetrical wide beam distribution with high lumen output
- Silicone gasket seal on trim to heatsink and cable gland provide a totally sealed downlight with IP65 protection
- Installation springs suitable for ceiling thickness up to 20mm

OPTICAL & THERMAL PERFORMANCE

- Reflector, diffuser and efficient heatsink provides premium optical and thermal performance
- Efficient optical control in wide beam angle and no harsh cut off and ultra low glare
- Complies thermally with IC-4 and IC-F classification in accordance with AS/NZS 60598 (13W and 22W product only)

ELECTRICAL SYSTEM

- Supplied standard with a remote leading and trailing edge mains dimmable driver (refer to dimming options table)
- All drivers come with a quick-connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz


TECHNICAL PERFORMANCE

- 13W or 22W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ is available upon request

CODE ORDERING GUIDE: PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1192-3K-13W-01 or 1192-3K-13W/DALI-01

SYSTEM POWER	COLOUR TEMP.	60° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		60°
13W	3K	1192-3K-13W	1589	1173
	4K	1192-4K-13W	1760	1201
	5K	1192-5K-13W	1578	1047
22W	3K	1192-3K-22W	2533	1840
	4K	1192-4K-22W	2814	1874
	5K	1192-5K-22W	2519	1655



DIM CODE	OPTIONS	13W	22W
/DALI	Dali Dimming / Switch Dim	✓	✓
/DSI	Digital Dimming	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓
/DIM	Leading & Trailing edge	Std	Std

COLOUR CODE	Colour
-01	Satin White
-06	Matte Black

TOTALLY SEALED UNIT WITH CABLE GLAND FITTED FOR IP65 PROTECTION

