

1537

ACCENT



SPECIFICATIONS:

Forward throw
 1.8 kg
 CRI 82+
 CRI 70+
 Class I
 IP54
 CE
 5 Year warranty
 Made in Australia

CONSTRUCTION & DESIGN

- Surface mounted LED exterior forward throw wall light
- Constructed in die cast aluminium alloy and finished in durable polyester powder-coat paint
- Tempered frost glass cover silicone gaskets and stainless steel fasteners provide IP54 protection
- Efficient forward throw optics with efficient cut off control ensures almost no-upward illumination

OPTICAL & THERMAL PERFORMANCE

- LED thermal management incorporates both conduction and natural convection to transfer heat rapidly away from LED source to achieve maximum life of LED
- High efficiency optics for brilliant optical control and excellent vertical illumination with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with an integral leading and trailing edge mains dimmable driver and terminal block (refer to dimming options table)
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 13W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (macAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ is available upon request

CODE ORDERING GUIDE: / -

Example: 1537-3K-13W-03 or 1537-3K-13W/DALI-03

SYSTEM POWER	COLOUR TEMP.	74x69° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		
13W	3K	1537-3K-13W	1519	851
	4K	1537-4K-13W	1607	896
	5K	1537-5K-13W	1568	873

DIM CODE	OPTIONS	13W
/DALI	Dali Dimming	✓
/DSI	Digital Dimming	×
/AD	Analogue Dimming 1-10V	×
/DIM	Leading & Trailing edge	Std

COLOUR CODE	
-03	Textured White
-07	Textured Black
-11	Textured Silver

