

1645

FLASH LV



SPECIFICATIONS:

Forward throw
 0.8 kg
 CRI 82+
 Class I
 IP54
 CE
 5 Year warranty

CONSTRUCTION & DESIGN

- Recessed LED exterior wall light
- Constructed in pressure die cast aluminium alloy and finished in durable polyester powder-coat paint
- Robust housing for superior durability
- Recessed luminaire with glare free illumination
- Frosted tempered glass, silicone seals and stainless steel fasteners provide IP54 protection
- Plastic installation box included with each fitting to facilitate installation and maintenance
- Louvered front trim provides 60° forward throw illumination

OPTICAL & THERMAL PERFORMANCE

- LED thermal management incorporates conduction to transfer heat rapidly away from LED source with optimal performance

ELECTRICAL SYSTEM

- Supplied standard with an integral non-dimmable driver and terminal block
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 12W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (macAdam step) - 2
- Available in 3K or 4K colour temperature with low colour shift over time


CODE ORDERING GUIDE:

PRODUCT CODE - COLOUR CODE

Example: 1645-3K-12W-07

SYSTEM POWER	COLOUR TEMP.	93x45° BEAM ANGLE		HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE			
12W	3K	1645-3K-12W		1053	155
	4K	1645-4K-12W		1065	160

COLOUR CODE	
-07	Textured Black
-11	Textured Silver



*All dimensions include recessing box

INSTALLATION BOX

